

Component - Plastics

E194560

ZHEN JIANG CHI MEI CHEMICAL CO LTD

DAGANG ECONOMICAL DEVELOPING ZONE, 18 HAN FENG RD, ZHENJIANG JIANGSU 212132 CN

D-1000

Modified Acrylonitrile Butadiene Styrene (ABS), "Polylac", furnished as pellets

	Min Thk	Flame			RTI	RTI	RTI
Color	(mm)	Class	HWI	HAI	Elec	Imp	Str
ALL	1.5	V-0	3	3	60	60	60
	3.0	V-0, 5VA	3	2	60	60	60

Comparative Tracking Index (CTI): **2**

Dimensional Stability (%): -

High-Voltage Arc Tracking Rate (HVTR): **3**

High Volt, Low Current Arc Resis (D495): **7**

Dielectric Strength (kV/mm): -

Volume Resistivity (10^x ohm-cm): -

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2004-01-09

Last Revised: 2009-09-10

Underwriters Laboratories Inc®

